

HAND OPERATED SUCTION PUMPS

For the extraction
or transfer of fluids



Available versions

HAP 125	Ref. No. 060414
HAP 125DL	Ref. No. 060414_2
HAP 250	Ref. No. 060415_1
HAP 250DL	Ref. No. 060415_2
HAP 600	Ref. No. 060412_1
HAP 600DL	Ref. No. 060412_2
HAP 600F	Ref. No. 060412_3
HAP 3000F	Ref. No. 060413_1

DESCRIPTION:

- Suitable for fluids such as diesel fuel, heating oil, engine oil, brake fluid and water.
- Available pump capacities: 125 ml, 250 ml, 600 ml, 3300 ml
- Available in a robust, all aluminium version or in a high strength plastic/aluminium version
- Hoses permit the connection of almost all containers and lines

**HAP double stroke pumps
convey fluid with every pumping action.
No 'dry' pump strokes!**

OTHER ADVANTAGES:

- If required, available with a baseplate for stability when in use (600 ml and 3300 ml versions)
- Totally rebuildable, spare parts available



DIN EN ISO 9001:2000
Reg.no. 12 100 24343 TMS

Autotestgeräte
Leitenberger GmbH
Bahnhofstraße 33
D-72138 Kirchentellinsfurt
Germany
WWW.LEITENBERGER.DE

FOR MORE INFORMATION, PLEASE CONTACT:

Phone: +49 (0)7121/908-101
Fax: +49 (0)7121/908-200
E-Mail: atg-info@leitenberger.de

WWW.AUTOTESTGERAETE.DE